

# Sri Vasavi Shrink Films - PET-G Shrink Sleeves

TECHNICAL SPECIFICATIONS & HIGH CONTOUR WRAPPING

ISO 9001:2015 Certified Manufacturer | Hyderabad, India

---

## Core Technical Parameters:

- Thickness Profile: 40 to 50 Microns (+/- 4% tolerance)
- Maximum Shrinkage (TD): Up to 78% (at 95 degrees C hot water/steam)
- Density: 1.32 g/cm<sup>3</sup> (ASTM D1505)
- Puncture Force Resilience: > 12 N (ASTM F1306)
- Gloss Value: > 90 Units (ASTM D2457 at 45 degrees)

## Key Industrial Applications:

- Contour Juice Bottles & Craft Sodas
- Highly Convex or Concave Curved Glass Containers
- Tamper-Evident Safety Neck Seals & Full Body Sleeves

## Eco-Friendly Advancements:

- Fully recyclable base compounds for sustainability goals.
- Excellent printing surfaces for high-end metallic and matte finishes.

Contact Sales: [sales@srivasavishrinkfilms.com](mailto:sales@srivasavishrinkfilms.com) | [info@srivasavishrinkfilms.com](mailto:info@srivasavishrinkfilms.com)

Visit Us: [www.srivasavishrinkfilms.com](http://www.srivasavishrinkfilms.com)

Developed By Yash Host ([yash-host.in](http://yash-host.in))